



# S1i

## SINGLE PRINTHEAD

### HP TIJ2.5 THERMAL INKJET PRINTER

- ✓ **HIGH SPEED**  
Print upto 76m/min
- ✓ **SIMPLE, INTUITIVE OPERATION**
- ✓ **TEXT, BARCODES & LOGOS**
- ✓ **FOOD PROCESSING, COSMETICS & PHARMACEUTICAL**

**Enhanced flexibility & adaptability**





POLYMER THERMAL INKJET TECHNOLOGY

DISTINCTLY DIFFERENT DIGITAL

# S1i

## SINGLE PRINTHEAD

HP TIJ2.5 THERMAL INKJET PRINTER

The POLYtj<sup>®</sup> S1i HP thermal inkjet printer offers high-resolution printing and incredibly simple operation & low cost performance.

The user interface is simple enabling operators to quickly enter text, barcodes & logos if required.

Like all POLYtj<sup>®</sup> printers, the printer comes with a large and unique range of inks that can print onto both most porous & non porous substrates used in the fast moving consumer goods market.

**Low cost option,  
flexible and reliable**

**DISTRIBUTED BY:**



### Technical Specification

Specification	Controller: 151*93*32mm (H*W*D) / 5.9*3.7*1.3 inch Printhead: 175*52*33mm (H*W*D) / 6.9*2.0*1.3 inch
Language	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	50-600dpi
Counters	Series No, Carton No, Pallet No etc
Printable heights (mm)	1-12.7mm
Printing speed	0-60 m/min(300 DPI)    0-30 m/min(600 DPI)
Production Speed	Production speed can be set as requested, automatic calculation and external synchroniser
Barcode	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128 PDF417, DATAMATRIX, QR
Date format	Production date, expiry date with several formats for option
Interface	5inch 800*480 resolution color LCD touch screen
Port	1) Ethernet: Support PC software communication protocol/SDK 2) USB2.0: Support U-Disk 3) DB15: For external devices like photocell, synchronizer or alarm kit connection
Ink management	Identify ink type automatically and recommend the best printing parameter Original authentic HP ink cartridge guaranteed Automatic measuring system for ink consumption
Installation	Standard side printing bracket, down printing bracket and anti-shock bracket, users can install according to their needs, spring mechanism is optional
Power supply	AC 100V-240V 50-60HZ,30 W (Specified AC adaptor)
Certificate	CE, FCC

DIGITAL INK TECHNOLOGIES PTY LTD  
1&2, 74 MASON STREET,  
CAMPBELLFIELD, VICTORIA, 3061  
AUSTRALIA  
www.digitalinktechnologies.com.au  
dit1161@me.com  
+61393575533

