

Distinctly Different Digital



illumex[®]

X2 X4 ECONOMIC

HP TIJ2.5 THERMAL INKJET PRINTER



COST EFFECTIVE
Economic model with high
print stability



HIGH RELIABILITY
Unique nozzle control
Real time temperature control
Alternate nozzle printing
Higher print quality, longer
service life



FLEXIBLE OPTIONS
Horizontal dpi - 50 to 1200dpi
Resolution 600 x 1200dpi
Function -Communication
- I/O customisation

Printer Options: Two Printheads



Four Printheads



60
m/m

600
dpi

1 to 4
Heads

Variable
data

EASY
use

Parameters:

	illumex - X4	illumex - X2
Technology	HP TIJ2.5 Thermal Inkjet Technology	HP TIJ2.5 Thermal Inkjet Technology
Resolution	Vertical: 600dpi Horizontal dpi 40-1200dpi (single head)	
Communication Protocol	Plain code protocol, easy system integration and secondary development.	
Screen	7 inches color capacitance screen	7 inches color capacitance screen
Dimensions	Controller: 211*125*43mm	Controller: 211*125*43mm
	Print head: 156*49*93mm	Print head: 156*49*93mm
Language	Chinese, English, Korean, Spanish, Japanese, French, German, Italian, Turkish	
Keyboard	Chinese, English, Korean, Arabic, Russian, Spanish, French, German	
Counter	Ordinary counter, the carry bit source setting flexibly	
Printing Height	1~50.8mm (Four printheads, Separate or combine at will)	1~25.4mm (Two printheads, Separate or combine at will)
Printing Speed	Up to 60m/min	
Printing Performance	The speed of QR code printing up to 5pcs/sec.	
Supported Barcode	1.Codebar 2.Code25 3.Code39 4.Code93 5.Code128 6.UPCA 7.UPCE 8.EAN 1.QR Code 2.Data Matrix GS1 3.Grid Matrix 4.Maxicode 5.PDF417	
Date Format	The date mode setting flexibly,User-defined the format.	
Interface	Ethernet interface*1	
	USB interface*1(USB flash drive and auxiliary communication equipment available)	
	DVI interface: connect to cable box or extended cable box Cable box interface: alarm kit, photocell, encoder, I/O (2 inputs 2 outputs) RS232	
	Extended cable box interface: alarm kit, photocell, encoder, I/O (6 inputs 5 outputs) RS232 DC interface: power cable DB15 interface: connect with printhead *4	
Ink Management	Recognize the ink type and choose the most suitable parameters automatically Only original HP cartridges are supported; Automatic measurement system for ink consumption	
Set up	Equipped with side printing/down printing bracket can be combined installation at will, optional Spring-back mechanism	
Environment Requirements	Operating environment: -10°-55° ; 10%-95%RH	
	Storage environment: -20°- 70°; 10%-95%RH	
Input Power	100-240V~50/60Hz 1.5A 120VA	
Output Power	24V 4A 96W	
Product Certification	CE FCC	



“ Coding and marking options for most all products used in the fast moving consumer goods market ”